

MAGNETIC STRIPE

Readers & Cards



- Suitable for Internal and External Use
- Proven technology
- ISO Track 2 (Trk1 available)
- Connect directly to P1, P3 or P4 access controllers
- Photo ID bureau service available
- Print & encode your own cards with Doors Enterprise software

Introduction

All Magnetic stripe readers are Track 2 as standard. Readers for Track 1 or Track 3 are available, please contact Sales for more information.

Cards with HI-CO or LO-CO magnetic stripes may be used. However it is recommended that HI-CO cards be used for access control. All Progeny magnetic stripe cards are HI-CO.

Use 8 core screened cable (maximum 100m length) for the magnetic stripe readers.

2075

EXTERNAL MAGSTRIPE READER

Swipe reader for outdoor use, can also be used indoors. All the electronics are embedded in epoxy resin making it weather-proof.

The reader head provides an extremely reliable reading capability with over 1 million head passes.

The 2075 reader is made from an ultra-tough UV resistant polycarbonate, making the product very durable and ensuring that even the harshest conditions the reader continues to work.

The tri-colour LED provides a visual indicator-showing the current reader status, whilst the internal buzzer provides an audible indicator. Both indicators are utilised via external lines.

The reader comes complete with 2.5m of screened 8 core cable, alan key and screws.

Specification

Supply Voltage	+12V
Current consumption	20mA @ +12V DC
Weatherproof	-25°C to +65°C (-13°F to +150°F)
Cable type	8 Core Screened
Maximum cable length	100 metres
Reader Life	1,000,000 Swipes
Dimensions	112 x 42 x 36 mm

Product Codes

Description	Code
External Magnetic Stripe Reader	2075
Mono (Hi Co) Magnetic Stripe Card	2014
Colour (Hi Co) Magnetic Stripe Card	2015
Cleaning Cards (10 pack)	2150

